

Deeztek Hosted Mail DNS entries

The following entries must be set in customer's domain DNS records in order for Hosted Mail to function correctly. The name **domain_tld** refers to the customer domain but instead of a . (dot) to separate the Top Level domain (TLD), substitute with a _ (underscore). For example, if domain is **mycompany.com** then the entry should be **mycompany_com**.

Name	Type	Priority	Weight	Port	TTL	Value
autodiscover	CNAME				60	mail.hosting.deeztek.com
autoconfig	CNAME				60	mail.hosting.deeztek.com
mail._domainkey	CNAME				60	dkim_ domain_tld .hosting.deeztek.com
@	MX				60	smtp.deeztek.com
_imap._tcp	SRV	0	0	143	60	mail.hosting.deeztek.com
_imaps._tcp	SRV	0	0	993	60	mail.hosting.deeztek.com
_pop3._tcp	SRV	0	0	110	60	mail.hosting.deeztek.com
_pop3s._tcp	SRV	0	0	995	60	mail.hosting.deeztek.com
_submission._tcp	SRV	0	0	587	60	mail.hosting.deeztek.com
_smtps._tcp	SRV	0	0	465	60	mail.hosting.deeztek.com
_sieve._tcp	SRV	0	0	4190	60	mail.hosting.deeztek.com
_autodiscover._tcp	SRV	0	0	443	60	mail.hosting.deeztek.com
_carddavs._tcp	SRV	0	0	443	60	mail.hosting.deeztek.com

_caldavs._tcp	SRV	0	0	443	60	mail.hosting.d eeztek.com
_carddavs._tcp	TXT				60	"path=/SOG o/dav/"
_caldavs._tcp	TXT				60	"path=/SOG o/dav/"
@	TXT				60	"v=spf1 mx a a:smtp.d eeztek.com ~all"
_dmarc	TXT				60	"v=DMARC1; p=quarantine; rua=mailto:d marc- domain_tld @deeztek.com ; ruf=mailto:po stmaster@dee ztek.com; fo=0; adkim=r; aspf=r; pct=100; rf=afrf; ri=86400"

Revision #3

Created 30 June 2022 13:36:14 by Dino Edwards

Updated 13 October 2022 10:33:56 by Dino Edwards