

Deeztek Hosted Mail DNS entries

The following entries must be set in customer's domain DNS records in order for Hosted Mail to function correctly. The name **domain_tld** refers to the customer domain but instead of a . (dot) to separate the Top Level domain (TLD), substitute with a _ (underscore). For example, if domain is **mycompany.com** then the entry should be **mycompany_com**.

Name	Type	Priority	Weight	Port	TTL	Value
autodiscover	CNAME				60	mail.hosting.deeztek.com
autoconfig	CNAME				60	mail.hosting.deeztek.com
mail_domainkey	CNAME				60	dkim_domain_tld.hosting.deeztek.com
@	MX				60	smtp.deeztek.com
_imap_tcp	SRV	0	0	143	60	mail.hosting.deeztek.com
_imaps_tcp	SRV	0	0	993	60	mail.hosting.deeztek.com
_pop3_tcp	SRV	0	0	110	60	mail.hosting.deeztek.com
_pop3s_tcp	SRV	0	0	995	60	mail.hosting.deeztek.com
_submission_tcp	SRV	0	0	587	60	mail.hosting.deeztek.com
_smtps_tcp	SRV	0	0	465	60	mail.hosting.deeztek.com
_sieve_tcp	SRV	0	0	4190	60	mail.hosting.deeztek.com
_autodiscover_tcp	SRV	0	0	443	60	mail.hosting.deeztek.com
_carddavs_tcp	SRV	0	0	443	60	mail.hosting.deeztek.com

_caldavs._tcp	SRV	0	0	443	60	mail.hosting.d eeztek.com
_carddavs._tcp	TXT				60	"path=/SOGo/ dav/"
_caldavs._tcp	TXT				60	"path=/SOGo/ dav/"
@	TXT				60	"v=spf1 mx a a:smtp.deezte k.com ~all"
_dmarc	TXT				60	"v=DMARC1; p=quarantine; rua=mailto:d marc- domain_tld @deeztek.com ; ruf=mailto:po stmaster@dee ztek.com; fo=0; adkim=r; aspf=r; pct=100; rf=afrf; ri=86400"

Revision #3

Created 2022-06-30 13:36:14 UTC by Dino Edwards

Updated 2022-10-13 10:33:56 UTC by Dino Edwards